

mblights.com.au Q

1300 MB LIGHTS // 1300 62 544 487 info@mblights.com.au

EMERGENSEETMONE D40 LED - RECESSED MOUNTED NON-MAINTAINED ALL IN-ONE EMERGENCY LIGHT

The EmergenSee[™] One takes advantage of innovative technology to integrate a lifetime-warranted ultra-bright LED, intelligent controls, and high capacity battery into one compact and aestheticallypleasing unibody chassis.

This ceiling-recessible emergency light provides dependable and distinct illumination when it is needed the most can suits almost all internal general applications including offices, shopping centres, commercial properties, and residential buildings.





Project Name	Туре	Qty
Comments		

Technical Specifications


MB LIGHTS


ltem	Part Number	EMS-ONE
	Description	D40 LED Recessed All-in-One Non-Maintained Emergency Light c/w Synthium™ Battery
Input	Voltage & Frequency	230VAC ; 50Hz
	Installation	Complete with 1.2m flex cable & plug
Output	Light Source	High performance LED - lifetime warranty
	-	
	Mode of Operation	Non-Maintained
	Power Consumption	2W (standby)
	Emergency Duration	> 120 minutes
	Chammen .	
Controls	Charger	16hr intelligent 3-stage charger with Synthium™ battery management system
	Protection	Overcharge, low voltage disconnect, overcurrent, short circuit
	Testing Facility	Manual test switch
	Indicators	Battery charger green LED
Physical	Construction	Flame-retardant polycarbonate
	Mounting	Recessed - ceiling, 70 - 150mm cut-out
	Dimensions L x W x H	Disc: 100mm or 160mm diameter
	IP Rating	IP 20
	Weight	1.0kg
	Warranty	5 years on product
Environment	Operating Temperature	1° to 40°C
	Relative Humidity	0 to 95%
Compliance	Standards	RCM / EMC, AS/NZS 2293, AS/NZS 60598.1
	AS/NZS 2293 Classification	C0 D40 C90 D40
Accessories	Replacement Battery	P/N° BAT-ONE' Synthium™ LiFePO

Accessories Replacement Battery P/N: BAT-ONE: Synthium™ LiFePO₄

NOTE: Product specifications subject to change without prior notice due to ongoing product improvement policy and changes to industry standards.

Dimensions





AS/NZS 2293.1:2018 Spacing Table

SPACING TABLE	MOUNTING HEIGHT (m)								
NATA Classification	2.1	2.4	2.7	3.0	4.0	5.0	6.0	8.0	10.0
C0 - D40	11.5	13.2	14.8	16.5	20.1	21.2	22.1	23.0	23.0
C90 - D40	11.5	13.2	14.8	16.5	20.1	21.2	22.1	23.0	23.0

