



Backlit LED's
100% Directional light to maximise the brightness and efficiency



Colour changing switch to allow the flexibility of keeping the consistent fitting throughout with multiple colour options if you wish to change in time.



Suspension mounting option
Part No. MBL-BLP-SUSKIT

Electrical Information

Model No.	MBL-BLP6X6CCTPA
Power Consumption (±10%)	26 Watt / 30 Watt / 34 Watt / 38 Watt
Input Voltage	220-240VAC 50/60Hz
Power Factor	>0.90
UGR	<19
Beam Angle	110 Degrees
Control	Standard Non-Dimmable Optional extras - Triac Dimming & Dali Dimming

Optic Information

LED Type	Epistar
Luminous Flux (±10%)	2,470lm / 2,850lm / 3,230lm / 3,610lm
Efficacy (5000K Ra70)	95lm/w
Correlated Colour Temp	3000K/4000K/5700K
Colour Rendering Index	>80
UGR	<19

Dimensions and Mount

Dimensions	595x595x90mm
Mounting Option	Recessed Tile/Plaster, Surface Mounted & Suspended
Material	Extruded Aluminum with PMMA Lens
Finish	Powder Coating
Fixture Colour	White
IP Rating	IP20

Lifespan and Warranty

Operation Temperature	0°C ~ +40°C
Life Time of LED	50,000 hrs
Warranty	5 Year

Project Name

Type

Qty

Comments