



Electical Information	
Model No.	MBL-BLI25W-4K-BLK
Power Consumption (±5%)	25Watt
Power Supply	Lifid
Power Factor	>0.90
Surge Protection	1kV line-line, 2kV line-earth
Driver Type	Constant Current
Control	Dali
	Non Dimmable

Optic Information	
LED Type	LED 3030
Luminous Flux (±10%)	1,920lm
Efficacy (5000K Ra70)	80lm/w
Correlated Colour Temp	3000K, 4000K (5000K Optional)
Colour Rendering Index	>80
Beam Angle	R03201, R03202, R03203
UGR Level	N/A

Dimensions and Mount	
Dimensions	165 x 900mm (6.2kg)
Mounting Option	Mounting Kit with Anchor Bolts
Material	Aluminium Alloy & Polycarbonate Optical Lens
Finish	Powder Coating
Fixture Colour	Black
IK Rating	IK10
IP Rating	IP66

Lifespan and Warranty	
Operation Temperature	-30°C ~ +50°C
Life Time of LED @ Ta=25 °C	37,800 hrs-L90
	78,500 hrs-L80
Warranty	5 Year



Round House Side Shield
To reduce glare



Mounting Kit with Anchor Bolts

Project Name	Type	Qty
Comments		