




Anti bird spikes
Prevents birds landing on it keeping the Solar panel cleaner




Universal Bracket
Suitable for pole top mount
60mm Spigot
(Comes standard with fitting)



Wall Mount Bracket



Round Pole Mount



Square Pole Mount



Remote

Electical Information	
Model No.	MBL-SFL25W-BLK-5K
Power Consumption (±10%)	25 Watts
Power Supply	12-24 Volt
Operating Time	8-10 Hours Full Power, Intelligent Mode
Surge Protection	4kV
Driver Type	Constant Current
Control Options	Light Control Motion Sensor
	Time Control PIR Built In

Optic Information	
LED Type	SEOUL 5050
Luminous Flux (±10%)	4750lm
Efficacy (5000K Ra70)	190lm/w
Correlated Colour Temp	5000K (3000K, 4000K Optional)
Colour Rendering Index	>70
Beam Angle	60° x 156°
Optical Lens	Polycarbonate

Solar Panel & Battery Information	
Panel	Double Crystal Photovoltaic Panel
Solar Panel	18 Volt / 40Watt
Battery	Li-ion Battery 230.4WH, 12.8V 18AH
Charging Time	5.76Hrs
Charging Temperature	-0°C ~ +45°C
IK Rating	IK08
IP Rating	IP65

Lifespan and Warranty	
Operation Temperature	-10°C ~ +60°C
Life Time of LED @ Ta=25°C	50,000 hrs
Warranty	3 Years
Gross Weight	15.86kg
Recommended Install Height	5-7mt
Product Size	793mm x 365.5mm x 211.4mm

Project Name

Type

Qty

Comments